



TGIK.R11260 Roofing Systems, Uplift Resistance

[Page Bottom](#)

Roofing Systems, Uplift Resistance

[See General Information for Roofing Systems, Uplift Resistance](#)

METACRYLICS

R11260

142 N 27TH ST
SAN JOSE, CA 95116 USA

BASE/PLY SHEET SYSTEMS

1. Uplift Resistance: 105 PSF

Deck: — Min. 15/32 plywood APA rated sheathing.

Insulation: — Aluminum foil faced polyisocyanurate, min 1.5 in. thick, fastened to deck with No. 12 by 2-1/4 in. self-drilling, self-tapping, hex-washer-head coated steel screws with 3-5/16 in. diameter plastic plate manufactured by Buildex, Inc. Sixteen fasteners used per 4 by 8 ft. sheet or 1 fastener per 20 sq ft. of board. All joints covered with 2 in. wide foil faced tape.

Base Sheet Roof Covering: — 3 gal per 100 sq ft of Base Acrylic identified as "Metacrylics Acrylic BASE" with "Metacrylics Stitchbond Polyester" embedded while wet and an additional 2 gal per 100 sq ft additional Base Acrylic immediately applied over the polyester.

Ply sheets: — Applied in two layers - Metacrylic top coat identified as "Metacrylics Acrylic WHITE" applied at 2 gal/sq followed by an optional 2nd coat at 2 gal/sq. Curing time between plies to be 2 days.

Last Updated on 1999-08-27

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2006 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

