


The Wayback Machine - http://web.archive.org/web/20150314005414/http://www.metacrylics.com:80/application/over-tar-gravel-roofing


[Home](#)»[Application](#)»[Over Tar & Gravel Roofing](#)

Metacrylics® Application over Tar & Gravel Roofing

[Printer-friendly version](#)


BUR: "Built-Up Roofing" is usually 2-4 plies of roofing adhered with hot tar and loose gravel applied to the final layer for fire protection.

Tear off existing roof(s) (typically, roof tear-off companies charge about \$.35 to \$.50 per ft² to remove and dispose of the old roof) and install Metacrylics® per the [New Construction Specification](#). Note: Many advantages to removing the old roof(s) include reducing the weight of the roof from 6+ lbs. /ft² to 1 lbs. /ft², having a fully adhered system that can withstand 100 mph winds, easy to clean and maintain reflective cool roof benefits reduce energy consumption as much as 20%, and all penetration on the roof receive new flexible GEL & fabric reinforcement on all roof penetrations, skylights, vents, etc. that will never leak again. Metacrylics® Application Chart Application Rate per 1 Roofing SQ (100 sf). Please click on the yellow highlighted boxes below to see the application instructions.

A Class A Fire Rating over plywood requires either DensDeck® or Atlas FR Slipsheet. See '[New Construction](#)' for application information.

Warranty		Materials Required for 100 sq .ft. (1 Roofing Square)					
C=Coating M=Material NDL=Mat'l & Labor	Length	Spud or tear off gravel roof	Clear or Black Primer	Clear Acrylic BASE	Acrylic WHITE	Stichbond Poly Entire Roof	3-Course Penetrations etc.
Material	15-Year	Yes	1.5 gal	5 gal	3 gal	1-Ply	Yes
M/NDL	20-Year	Yes	1.5 gal	5 gal	5 gal	1-Ply	Yes
M/NDL	30-Year	Yes	1.5 gal	7.5 gal	8 gal	2-Ply	5-Course

Metacrylics® in Action



Visit our [YouTube Profile](#) to see videos of Metacrylics in Action.

Copyright ©2012 Metacrylics®. All right reserved.